

SuperDos

Non-Electric, Water-Driven, Proportional Injectors



Description	Product code
SuperDos 15 0.3%	113727R
SuperDos 15 2.5%	113702
SuperDos 15 5%	113203
SuperDos 20 0.3%	113228R
SuperDos 20 2.5%	113205
SuperDos 20 5%	113206
SuperDos 20 10%	113207
SuperDos 30 0.3%	113729R
SuperDos 30 2.5%	113209
SuperDos 30 5%	113210
SuperDos 45 0.3%	113230R
SuperDos 45 2.5%	113212
SuperDos 45 5%	113215

Maintenance Kits

Kit A: Dosage piston kit

Dosage piston and O-rings



Light Usage:
Change every 6-12 months

Medium Usage:
Change every 6 months

Heavy Usage:
Change every 3-4 months

Model	Product code
SuperDos 15-20-30-45 0.3%	012310
SuperDos 15-20-30-45 2.5%	011850V
SuperDos 15-20-30-45 5%	011852PV
SuperDos 20 10%	011138

Kit D: Check valve kit

Suction tube fitting assembly (poppet, O-ring, spring, fitting)



Change as needed

Model	Product code
SuperDos 15-20-30 0.3%	011463V
SuperDos 15-20 2.5%	011463V
SuperDos 30 2.5%	011461V
SuperDos 45 0.3%	011461V
SuperDos 15-20-30 5%	011462V
SuperDos 45 2.5%	011462V
SuperDos 45 5%	011849M

Kit E: Wear parts maintenance kit

Dosage piston,
O-rings, shaft,
inner cylinder,
check valve kit



Change
as needed

Model	Product code
SuperDos 15-20-30 0.3%	012312R
SuperDos 45 0.3%	012315R
SuperDos 15-20 2.5%	011833PV
SuperDos 30 2.5%	011831PV
SupreDos 15-20-30 5%	011836PV

Kit G: Complete lower end kit

Dosage piston,
shaft, outer
cylinder, ratio
adjuster, O-rings,
pin, filter, solution
tube



Change
as needed

Model	Product code
SuperDos 15 - 20 - 30 0.3%	012314R
SuperDos 15 - 20 2.5%	011843PV
SuperDos 30 2.5%	011841PV
SuperDos 15 - 20 - 30 5%	011846PV
SuperDos 45 0.3%	012317R
SuperDos 45 2.5%	011847PV
SuperDos 45 5%	011848PV

Kit H: Motor piston kit

Motor piston assembly



Change
as needed

Model	Product code
SuperDos 15 0.3%	
SuperDos 15 2.5%	011863TF
SuperDos 15 5%	
SuperDos 20- 30 0.3%	
SuperDos 20 -30 2.5%	011863
SuperDos 20 - 30 5%	
SuperDos 20 10%	011879T
SuperDos 45 0.3%	
SuperDos 45 2.5%	011861
SuperDos 45 5%	

*All references with standard Viton seals. For other seal materials please contact your Hydro distributor.

**Images for information purposes only. Kits may have slight variations depending on the model.

***For HAC models, contact your sales representative.

Definitions

Light Usage: Pump is used once a week

Medium Usage: Pump is used 3-4 times each week

Heavy Usage: Pump is used 24 hours a day, seven days a week



Hydro Systems
3798 Round Bottom Road
Cincinnati, OH 45244

Phone 513.271.8800
Toll Free 800.543.7184
Fax 513.271.0160
Web hydrosystemsco.com